Ductile-Iron Pipe and Fittings

AWWA MANUAL M41

Third Edition



Copyright © 2009 American Water Works Association. All Rights Reserved.

Manual of Water Supply Practices — M41, Third Edition Ductile-Iron Pipe and Fittings

Copyright © 1996, 2003, 2009, American Water Works Association

All rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopy, recording, or any information or retrieval system, except in the form of brief excerpts or quotations for review purposes, without the written permission of the publisher.

The authors, contributors, editors, and publisher do not assume responsibility for the validity of the content or any consequences of its use. In no event will AWWA be liable for direct, indirect, special, incidental, or consequential damages arising out of the use of information presented in this book. In particular, AWWA will not be responsible for any costs, including, but not limited to, those incurred as a result of lost revenue. In no event shall AWWA's liability exceed the amount paid for the purchase of this book.

AWWA Publications Manager: Gay Porter De Nileon Project Manager/Copy Editor: Martha Ripley Gray Technical Editors: Tim McCandless (AWWA) and Richard Bonds (DIPRA) Production Editor: Darice Zimmermann, Zimm Services Manuals Coordinator: Beth Behner

Library of Congress Cataloging-in-Publication Data

Ductile-iron pipe and fittings. — 3rd ed. p. cm. — (Manual of water supply practices ; M41) Includes bibliographical references and index. ISBN 978-1-58321-632-3

1. Water-pipes 2. Cast-iron pipe. 3. Pipe fittings I. American Water Works Association.

TH491.D84 2009 628.1'5—dc22

2008038290

Printed in the United States of America American Water Works Association 6666 West Quincy Avenue Denver, CO 80235-3098

ISBN 978-1-58321-632-3



Contents

List of Figures, vii		
List of '	Tables, xi	
Preface	e, xiii	
Acknov	vledgments, xv	
Chapte	r 1 General Information and History 1	
1.	1 History, 1	
1.	2 Applications and Appurtenances, 3	
1.	3 Ductile Iron Pipe Research Association (DIPRA), 5	
Chapte	r 2 Applicable Standards	
2.	1 Related Standards, 7	
2.		
R	eferences, 10	
Chapte	r 3 Manufacturing and Testing 13	
3.	1 Manufacturing, 13	
3.	2 Testing, 17	
3.	3 Fittings Testing, 19	
R	eferences, 20	
Chapte	r 4 Design	
4.	1 Background, 21	
4.	2 Major Design Criteria and Formulas, 22	
4.	3 Truck Loads on Pipe Buried at Shallow Depths, 38	
4.	4 Thickness Design for Ductile-Iron Pipe Under Railroads, 43	
4.	5 Thickness Design for Ductile-Iron Pipe on Supports, 45	
4.	6 Special Use Considerations, 57	
R	eferences, 58	
Chapte	r 5 Pipe Joints	
5.	1 Introduction, 59	
5.	2 Joints, 59	
5.	3 Gaskets, 64	
5.	4 Joint Accessories, 64	
5.		
R	eferences, 66	

Chapter 6	Ductile- and Gray-Iron Fittings			
6.1	Introduction, 67			
6.2	Fittings, 67			
6.3	Special Service Requirements, 70			
Refer	rences, 71			
Chapter 7	Valves and Hydrants 73			
7.1	Introduction, 73			
7.2	Types of Valves and Hydrants, 73			
7.3	Installation, 76			
7.4	Operation, 76			
7.5	Good Practice, 77			
Refer	rences, 77			
Chapter 8	Thrust Restraint Design for Ductile-Iron Pipe 79			
8.1	Introduction, 79			
8.2	The Thrust Force, 81			
8.3	Thrust Blocks, 82			
8.4	Restrained Joints, 85			
8.5	Restraint Design for Vertical Bends, Tees, Reducers, and Dead Ends, 93			
8.6	Encroaching Restrained Lengths, 97			
8.7	Restrained Length, 99			
8.8	Select Backfill Considerations, 99			
8.9	Combining Thrust Blocks and Restrained Joints, 101			
8.10	Pipe in a Casing, 101			
8.11	Future Excavations, 101			
8.12	Deflected Unrestrained Ductile-Iron Pipe Joints, 101			
8.13	Computer Program, 102			
8.14	Restrained Length Calculation Procedure, 102			
8.15	Tabular Values for F_s , $(F_s)_b$, and R_s , 103			
	Restrained Joint Design Tables for Horizontal Bends, 104			
Refer	rences, 147			
Chapter 9	Interior Linings and Hydraulics 149			
9.1	Cement–Mortar-Lined Ductile-Iron Pipe, 149			
9.2	Flow Characteristics of Ductile-Iron Pipe, 153			
9.3	Pumping Cost, 155			
Refer	rences, 164			
Chapter 10 External Corrosion Protection				
10.1	Introduction, 165			
10.2	Basic Corrosion Theory, 166			
10.3	Corrosion Resistance of Ductile-Iron Pipe, 172			
10.4	Evaluation of Corrosive Soils, 173			

	10.5	Buried Service—Corrosion Control, 175
	10.6	Exposed Service Conditions, 188
	10.7	Submerged Service Conditions and Control, 192
	Refer	ences, 193
Chap	ter 11	Installation of Ductile-Iron Pipe 195
	11.1	Introduction, 195
	11.2	Pipe Inspection, Storage, Handling, and Delivery, 195
	11.3	Trenching, Embedment, Pipe Installation, and Backfilling, 197
	11.4	Pipeline Accessories, 209
	11.5	Thrust Restraint, 212
	11.6	Flushing, Field Testing, and Disinfection, 212
	11.7	Service Taps, 215
	11.8	Highway and Railroad Crossings, 220
	11.9	Trenchless Applications, 220
	11.10	Subaqueous Installations, 220
	11.11	Other Installations, 222
	Refer	ences, 225
Chap		Trenchless Installation— Iorizontal Directional Drilling227
		Introduction, 227
		Predesign Investigation, 229
	12.3	HDD Assembly Methods for Flexible Restrained-Joint
		Ductile-Iron Pipe, 230
	12.4	Survey, 232
	12.5	Subsurface Analysis, 232
	12.6	Borepath Design, 234
	12.7	Pipe Design: Introduction, 235
	12.8	Testing and Service Pressure/Loads, 238
	12.9	Thermal Expansion/Contraction and Pulling Load "Recoil," 239
	Refer	ences, 239
Chap	ter 13	Guidelines for Purchase of Pipe and Fittings241
	13.1	General, 241
	13.2	Ductile-Iron Pipe, 243
	13.3	Ductile-Iron and Gray-Iron Fittings and Specials, 244
	13.4	Polyethylene Encasement, 244
	Refer	ences, 245
Appe	ndix A	A Illustrations of Proprietary Joints for Ductile-Iron Pipe and Fittings
Index	.	
AWW	A Mar	uals

This page intentionally blank.

Figures

- 1-1 A 48-in. ductile-iron pipe water transmission main, 4
- 3-1 Elements of a casting machine, 15
- 3-2 Pipe entering an annealing oven, 16
- 3-3 Vertical annealing furnace, 17
- 3-4 Hydrostatic testing of pipe to a minimum of 500 psi (3,450 kPa), 18
- 4-1 Performance test on 36-in. (914-mm) ductile-iron pipe with push-on joints, 22
- 4-2 Laying conditions for ductile-iron pipe, 25
- 4-3 Truck loading conditions—single-wheel load, 39
- 4-4 Pipe loading from uniformly distributed railroad loading, 43
- 4-5 Railroad loading for Cooper E-80 locomotives, 43
- 4-6 Ductile-iron pipe is well suited for pipe-on-supports applications because of its beam strength, 47
- 4-7 Saddle angle and width, 47
- 5-1 Push-on, mechanical, and flanged joints, 61
- 5-2 Flanged joint details, 61
- 5-3 Flanged ductile-iron pipe and fittings in a water treatment plant, 62
- 5-4 Installation of mechanical-joint-type restrained joints, 63
- 6-1 Welded-on push-on joint outlet, 68
- 6-2 Ductile-iron fittings stacked in a storage yard, 69
- 7-1 Installation of a large-diameter gate valve, 74
- 7-2 Swing-check valves in a pump discharge line, 75
- 8-1 Push-on joint detail, 79
- 8-2 Thrust forces at joint of straight pipe, 81
- 8-3 Thrust forces at bend, 82
- 8-4 Thrust forces on other pipe configurations or appurtenances, 83
- 8-5 Bearing block details, 84
- 8-6 Gravity thrust block, 86
- 8-7 Restrained joints in a buried piping system, 86
- 8-8 Schematic of pipe-soil behavior at horizontal bend (or vertical up-bend), 88
- 8-9 Unit normal forces on pipe, 91
- 8-10 Vertical down-bend diagram, 94
- 8-11 Reaction forces at tees, 96
- 8-12 Reaction forces for reducers, 96

- 8-13 Reaction forces at dead ends, 96
- 8-14 Equal angle vertical offset (θ°), 97
- 8-15 Combined horizontal equal angle bends (θ°), 100
- 8-16 Combined equal angle vertical offsets (θ°), 100
- 9-1 Cement–mortar-lined ductile-iron pipe, 150
- 9-2 Nomograph for pipe size, head loss, and discharge for ductile-iron pipe, 154
- 10-1 Chemical reactions in a typical galvanic corrosion cell, 167
- 10-2 Corrosion cell, 169
- 10-3 Electrolytic corrosion cell, 170
- 10-4 Typical stray current environment, 170
- 10-5 Alternate polyethylene encasement installation methods, 177
- 10-6 Installation of polyethylene encasement using Method A, 178
- 10-7 Peened surface of a deLavaud pipe mold, 182
- 10-8 Close-up photograph of the cast surface of a typical ductile-iron pipe made by the deLavaud process, 182
- 10-9 Scanning electron microscope photomicrograph of a ductile-iron pipe surface profile. The layers consist of a 135- to 143-µm (5- to 6-mil) thickness of annealing oxide with underlying ductile iron, 183
- 10-10 Schematic diagram of a typical cross section of a ductile-iron pipe, 183
- 10-11a Annealed ductile-iron pipe before over-blasting, 184
- 10-11b Same ductile-iron pipe resulting in blisters and disbondment from over-blasting, 184
- 10-12 Typical risk model, 188
- 11-1 Unloading pipe with a forklift, 196
- 11-2 Unloading pipe with a crane, 197
- 11-3 Installing small-diameter ductile-iron pipe in a narrow trench, 200
- 11-4 Because of its ruggedness, ductile-iron pipe is particularly suitable for installation in demanding environments, 200
- 11-5 Polyethylene-encased ductile-iron pipe, 201
- 11-6 Laying conditions for ductile-iron pipe, 203
- 11-7 Push-on joint assembly, 204
- 11-8 Mechanical joint assembly, 205
- 11-9 Sweeping curves without fittings and specials are possible because of liberal joint deflection allowance by ductile-iron pipe push-on joints, 206
- 11-10 Pipeline curve geometry, 208
- 11-11 Cutting pipe with an abrasive wheel saw, 208
- 11-12 Installing valves and fittings, 210
- 11-13 Installation of a 48-in. (1,219-mm) butterfly valve, 211
- 11-14 Fire hydrant installation, 213

- 11-15 Direct service connection tapped through polyethylene adhesive tape and polyethylene film, 217
- 11-16 Ball-and-socket ductile-iron pipe used in a subaqueous installation using the "chute" method, 221
- 11-17 Subaqueous pipe being floated into position, 221
- 11-18 Ductile-iron pipe installed on a bridge, 222
- 11-19 Ductile-iron pipe spanning waterway, 223
- 11-20 Pump station piping, 224
- 11-21 Ductile-iron pipe being installed in a deep trench, 224
- 12-1 Pilot bore, 227
- 12-2 Prereaming, 228
- 12-3 Pipe pullback, 229
- 12-4 Assembled line method, 231
- 12-5 Cartridge method, 231
- 12-6 Polyethylene encasement, 234
- 13-1 A full truck load of ductile-iron pipe, 243
- A-1 Push-on joints, 248
- A-2 Ball-and-socket joints, 248
- A-3 Grooved-and-shouldered joints, 249
- A-4 Restrained joints—push-on type, 249
- A-5 Restrained joints—mechanical joint and other joint type, 251

This page intentionally blank.

Tables

- 3-1 Acceptance values for tensile tests, 19
- 4-1 Reduction factors, *R*, for truck load calculations, 24
- 4-2 Design values for standard laying conditions, 27
- 4-3 Allowances for casting tolerance, 29
- 4-4 Standard pressure classes of ductile-iron pipe, 29
- 4-5 Rated working pressure and maximum depth of cover, standard pressure classes, 30
- 4-6 Special thickness classes of ductile-iron pipe, 32
- 4-7 Rated working pressure and maximum depth of cover, special thickness classes, 33
- 4-8 Earth loads P_{e} , truck loads P_{t} , and trench loads P_{v} (psi), 40
- 4-9 Surface load factors *C* for single truck on unpaved road, 40
- 4-10 Thickness for earth load plus truck load, 41
- 4-11 Surface load factors for Cooper railroad loading, 45
- 4-12 Pipe plus water weight $(W_p + W_w)$ and design wall thickness t_n , 50
- 4-13 Earth loads P_e and truck loads P_t (psi), 54
- 5-1 Gasket materials used for ductile-iron pipe in water and sewage service, 65
- 8-1 Horizontal soil-bearing strength, 84
- 8-2 Suggested values for soil parameters and reduction constant K_n , 87
- 8-3 Soil classification chart—ASTM Standard D2487, 90
- 8-4 Values for D', A, W_p, W_w , and $(W_p + W_w), 92$
- 8-5 Thrust restraint design for ductile-iron pipe for clay 1 soil type, 105
- 8-6 Thrust restraint design for ductile-iron pipe for silt 1 soil type, 108
- 8-7 Thrust restraint design for ductile-iron pipe for clay 2 soil type, 111
- 8-8 Thrust restraint design for ductile-iron pipe for silt 2 soil type, 114
- 8-9 Thrust restraint design for ductile-iron pipe for coh-gran soil type, 117
- 8-10 Thrust restraint design for ductile-iron pipe for sand silt soil type, 120
- 8-11 Thrust restraint design for ductile-iron pipe for good sand soil type, 123
- 8-12 Restrained joint lengths for horizontal bends for clay 1 soil type, 126
- 8-13 Restrained joint lengths for horizontal bends for silt 1 soil type, 129
- 8-14 Restrained joint lengths for horizontal bends for clay 2 soil type, 132
- 8-15 Restrained joint lengths for horizontal bends for silt 2 soil type, 135
- 8-16 Restrained joint lengths for horizontal bends for coh-gran soil type, 138

- 8-17 Restrained joint lengths for horizontal bends for sand silt soil type, 141
- 8-18 Restrained joint lengths for horizontal bends for good sand soil type, 144
- 9-1 Inside diameters and flow areas of the minimum available pressure classes of cementmortar-lined ductile-iron pipe, 156
- 9-2 Head loss in feet per 1,000 ft of pipe (6 in. to 12 in.), cement-mortar-lined ductile-iron pipe, nominal ID pipe, C = 140, 157
- 9-3 Head loss in feet per 1,000 ft of pipe (14 in. to 20 in.), cement-mortar-lined ductile-iron pipe, nominal ID pipe, C = 140, 157
- 9-4 Head loss in feet per 1,000 ft of pipe (24 in. to 36 in.), cement-mortar-lined ductile-iron pipe, nominal ID pipe, C = 140, 158
- 9-5 Head loss in feet per 1,000 ft of pipe (42 in. to 54 in.), cement-mortar-lined ductile-iron pipe, nominal ID pipe, C = 140, 158
- 9-6 Head loss in feet per 1,000 ft of pipe (60 in. to 64 in.), cement-mortar-lined ductile-iron pipe, nominal ID pipe, C = 140, 159
- 10-1 Galvanic series of selected metals and alloys (in seawater), 168
- 10-2 Soil-test evaluation for gray or ductile cast-iron pipe (10-point system), 174
- 11-1 Maximum stacking heights for ductile-iron pipe, 198
- 11-2 Suggested trench widths at the top of the pipe, 199
- 11-3 Mechanical joint bolt torques, 202
- 11-4 Maximum joint deflection full-length pipe—push-on type joint pipe, 207
- 11-5 Maximum joint deflection full-length pipe—mechanical type joint pipe, 207
- 11-6 Hydrostatic testing allowance per 1,000 ft (305 m) of pipeline (gph), 216
- 11-7 Pipe thicknesses required for different tap sizes as per ANSI/ASME B1.20.1 for standard taper pipe threads with two, three, and four full threads, 218
- 11-8 Pipe thicknesses required for different tap sizes as per AWWA C800 for standard corporation stop threads with two, three, and four full threads, 219
- 12-1 Recommended borepath reamed inside diameters, 228
- 12-2 HDD applications and rationale, 229
- 12-3 Use of HDD in various soil types, 233

This is the third edition of AWWA M41, *Ductile-Iron Pipe and Fittings*. This manual provides the user with both technical and general information to aid in the design, specification, procurement, installation, and understanding of ductile-iron pipe and fittings. It is a discussion of recommended practice, not an AWWA standard calling for compliance with certain specifications. It is intended for use by utilities and municipalities of all sizes, whether as a reference book or textbook for those not fully familiar with ductile-iron pipe and fitting products. Design engineers and consultants may use this manual in preparing plans and specifications for new ductile-iron pipe projects.

The manual covers ductile-iron pipe and fitting products and certain appurtenances and their application to practical installations, whether of a standard or special nature. For adequate knowledge of these products, the entire manual should be studied. Readers will also find the manual a useful source of information when assistance is needed with specific or unusual conditions. The manual contains a list of applicable national standards, which may be purchased from the respective standards organizations (e.g., AWWA, ASTM). Standards referenced in this manual refer to the latest editions.

Credit is extended to the Ductile Iron Pipe Research Association (DIPRA) for granting permission to reprint numerous graphics and tables found throughout this manual.